

Mandich 9-10 'Serial No. 09/912,129 Filing Date: July 24, 2001 790151-3A

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

61-183142

(43)Date of publication of application: 15.08.1986

(51)Int.CI.

CO3B 37/018 CO3C 13/04 // GO2B 6/00

(21)Application number: 60-024128

(71)Applicant: FUJIKURA LTD

(22)Date of filing:

09.02.1985

(72)Inventor: SHIODA TAKAO

HIDAKA HIROMI

FUKUDA TAKERU INADA KOICHI

(54) PRODUCTION OF GLASS CAPILLARY

(57)Abstract:

PURPOSE: To obtain a capillary for chromatography contg. a stationary phase with sufficient adhesive power and having a long life and high resolution by sintering a round rod-shaped preform of glass soot formed by a VAD method in the presence of a specified gas and by boring the resulting base material. CONSTITUTION: A round rod-shaped porous preform of SiO2 glass soot is formed on the tip of a starting rod by a VAD method, and it is sintered in an atmosphere of a gas contg. S and halogen such as SOCI2 or S2CI2

mixed with an inert gas such as N2. A gas contg. S such as SO2, SO3 or other S oxide and a gas contg. halogen such as Cl2, Br2 or F2 may be used in place of the gas contg. S and halogen. The resulting sintered body is bored to form a cylindrical glass pipe and a glass capillary is obtd. by melt-spinning the pipe.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]